



General Purpose Premium Lacquer

Product Description

Dupli-Color® General Purpose Premium Lacquer is a fast-drying, premium quality formula that provides quick coverage, weatherability and adhesion. Perfect for automotive trim and detail projects. It delivers a rich glossy finish every time.

Product Characteristics

Color: Flat Black, Semi-Gloss Black, Gloss White, Gloss Black, & Silver Metallic.

Clear: Crystal Clear

Finish: Gloss, Semi-Gloss, Flat, & Metallic.

Properties

Product Weight: 6.15 lb/gal

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color General Purpose Premium Lacquer provides optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
Prime	DAPxxxx	Sandable Primer
Coat	DALxxxx	Premium Lacquer
Clear	DAL1695	Crystal Clear

Sandable Primer is used when bare metal is exposed

Refer to the application box for more specific instructions!

Uses

Cars, Trailers, RV's, & Other Auto Accessories.

Surfaces:

Metal, Aluminum, Plastic, & Fiberglass.

Application

Do not use Dupli-Color Acrylic Lacquer over existing air-dried enamel paints.

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover. Sand surface with 320-grit sandpaper, wet or dry. Wash with mild soap and water. Rinse well, and dry with a clean cloth.

Mask-off surrounding areas to protect from overspray. If bare metal is exposed, prime surface first with Dupli-Color Sandable Primer. Allow primer to dry for at least one hour at 70° F, before applying Dupli-Color Acrylic Lacquer. Use at temperature between 60°- 92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to painted and use in an even, sweeping motion. To avoid runs and sags apply 2-3 light coats, allowing surface to dry 10 minutes between each coat. For added durability and improved gloss, apply Dupli-Color Clear Lacquer (DAL1695) over last color coat. Dries to touch in 30 minutes. Can be handled in one hour. Covers approximately 12-14 square feet.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.

Packaging

Fill Weight: 12 oz

Per Case: 6 cans

Case Weight: 6.07 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans