Dupli-Color® Stainless Steel Coating

Product Description

Dupli-Color® Stainless Steel Coating provides the brilliant and popular look of stainless steel to automotive accessories, such as trim, grills, and other bumpers. It dries quickly to durable finish and resists temperatures up to 250° F, allowing for under hood applications.

Features excellent adhesion to metal, wood, iron, glass, and most other surfaces.

Product Characteristics

Colors: Stainless Steel

Finish: Metallic

Properties

Product Weight: 6.31 lb/gal
Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Stainless Steel Coating provides optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax Remover
Coat	SS100	Stainless Steel

Use prep products before and after sanding!

Refer to the application box for more specific instructions!

Uses

Automotive Accessories (Ex: Trim, Grills, & Bumpers)

Surfaces:
Metal, Wood, Iron, Glass, & Most Other Surfaces.

Application

Removing the substrate from the vehicle is recommended for ease of application. Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. Use Grease & Wax Remover or Dupli-Color® Prep Spray PS100 to clean surface. Lightly sand surfaces with 600 grit sandpaper, wet or dry. Wipe surface down again with Dupli-Color® Prep Spray PS100. Mask off surrounding areas to protect from overspray.

Use at temperatures between 60° F (16° C) and 95° F (35° C), and when humidity is less than 60-70%. Dupli-Color Self-Etching Primer (DAP1690) is suggested.

Shake can vigorously for one full minute after mixing ball moves freely. Shake can for 10 seconds after each minute of use. To spray, hold can parallel 8-10 inches from surface to be painted and use in an even, sweeping motion. Apply Dupli-Color Stainless Steel in 2-3 light coats or as many needed to achieve desired results. Each coat can be applied after 10-15 minutes of dry time. Dries to the touch in 30 minutes. Can be handled in 1 hour. Any excess metallic flakes can be wiped off the substrate with a clean rag after 1 hour. Covers approximately 12-14 square feet

Note: This product is NOT intended as a touch-up for stainless steel surfaces.

Packaging

Fill Weight: 11 oz
Per Case: 6 cans
Case Weight: 5.8 lbs
Cases/Pallet: 156
Units/Pallet: 936 cans

(V.3, 12/12)