



Bed Armor™ Aerosol

BAA2010

Product Description

Dupli-Color® Bed Armor™ Aerosol is a water-based polyurethane coating formulated with ground up rubber particles to provide uniform texture and skid resistance. This offers the same durability and protection of Bed Armor.

Product Characteristics

Color: Black

Finish: Textured Satin

Properties

Product Weight: 8.3 lb/gal

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Bed Armor Aerosol provides an optimum performance when this application method is followed.

Prep	CM541	Grease & Wax Remover
	PS100	Prep Spray
	PW100	Prep Wipe
Coat	BAA2010	Bed Armor Aerosol

Refer to the application box for more specific instructions!

Uses

Cut-in or touch-up with Bed Armor Quart or Kit.

Surfaces:

Wood, Concrete, Fiberglass, Aluminum, & Metal.

Application

Clean truck bed and tailgate using a stiff brush or pressure washer. Use a strong household detergent or Grease & Wax Remover to thoroughly remove oils, chemicals, or other contaminants. Rinse clean and let dry.

Mask-off all hardware, drain plugs, and areas of the truck bed and tailgate you do not want BED ARMOR to bond to.

Using a scouring pad or 180-grit sandpaper, scuff all glossy areas of the truck bed. Scuffing glossy surfaces will ensure a superior bond to the surface. Use a broom or air hose to remove all sanding dust. Wipe down truck bed and tailgate with a Dupli-Color Grease and Wax Remover product.

Shake can vigorously for 1 full minute after mixing ball moves freely. After each minute of use, shake the can for 10 additional seconds. To spray, hold the can 12-15 inches from the selected surface to achieve a textured finish. Apply 3-4 light coats. Allow 20 minutes between coats and 1 hour before applying, BED ARMOR Gallon or Quart. Covers 16-18 square feet. Recoat at any time. Apply when conditions are dry and temperatures are over 50° F.

Packaging

Fill Weight: 16.5 oz

Per Case: 6 cans

Case Weight: 8 lbs

Cases/Pallet: 117

Units/Pallet: 702 cans