



Product Description

Dupli-Color® Shadow™ Black-Out Coating is a two-can system that creates the popular looks of black chrome on polished metal or chrome surfaces for cars, trucks, and motorcycles. It is resistant to brake dust, road abrasion, chipping, and fading.

Product Characteristics

Colors: Black Base Coat (Black tinted effect over chrome.)

Finish: High Gloss Finish

Properties

Product Weight: 6.26 lb/gal (Base)
6.30 lb/gal (Clear)

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Shadow Black-Out Coating provides optimum performance when this application method is followed.

Prep	CM541	Grease & Wax Remover
	PW100	Prep Wipe
Coat	SHD100	Black Base
Clear	SHD100	Clear Coat

Refer to application box for more specific instructions!

Uses

Chrome Wheels, Bumpers, Interior/Exterior Trim, Accessories, & Under Hood Components.

Surfaces:

Polished Metal or Chrome.

Packaging

Fill Weight: Two 11 oz cans

Per Case: 2 kits

Case Weight: 4 lbs

Cases/Pallet: 192

Units/Pallet: 384 cans

Application

For maximum product performance, read entire label and directions prior to paint application.

Base Coat

Prepare surface by removing dirt, wax, and grease using a quality Grease & Wax Remover.

Note: Shadow Base Coat is translucent. Do not sand surface unless desired effect is preferred.

Mask-off surrounding areas to protect from overspray. For best results, use at temperatures between 60° F (16° C) and 95° F (35° C), and humidity needs to be less than 70%.

Shake can vigorously for 1 full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. Apply Shadow Base Coat in 2-3 light coats or until desired effect is achieved. Each additional coat will provide a darker appearance. Allow 20 minutes between coats. Dries to the touch in 30 minutes. Can be handled in one hour.

Allow Shadow Base Coat 1 hour to dry. Topcoat using Dupli-Color Shadow Chrome Black-Out Clear Coat. Apply Clear Coat according to application instructions on clear-coat can.

Clear Coat

Apply Shadow Base Coat following the directions on the can. Allow one hour to dry, before applying Shadow Clear Coat.

Shake can vigorously for 1 full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. For best results, use at temperatures between 60° F (16° C) and 95° F (35° C), and humidity needs to be less than 70%.

To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. Apply Shadow Clear Coat in 2-3 light coats, allowing 20 minutes between coats. Dries to the touch in one hour. Covers approximately 12-14 square feet

Once the Dupli-Color Shadow Chrome Black-out coating system is complete, allow 4 to 5 hours or more of dry time before substrates are reinstalled or put use.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.