



Custom Wrap Metallic Series

CWRC830, CWRC831,
CWRC832, CWRC833

Product Description

Dupli-Color® Custom Wrap Metallic Series is specifically formulated for automotive customization. Custom Wrap provides a smooth, professional looking finish that resists the wear and tear of daily driving. To try a new color or go back to the original surface, this exclusive formulation also features our EZ Peel™ Technology for quick removal.

Product Characteristics

Color: Black Metallic, Aluminum, Blue Metallic and Gold

Finish: Matte

Properties

Product Weight: 6.29 lb/gal

Flash Point: -20 °F PMCC

Preferred Application

Dupli-Color Custom Wrap Removable Coating provides optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray

Coat	CWRCxxx	Custom Wrap
-------------	---------	-------------

Refer to the product label for more specific instructions!

Uses

Entire vehicle, accents, wheels, and more.

Surfaces:

Ideal for original factory painted finishes, aluminum, metal, chrome, and plastic.

Application

*Prepare surface by removing dirt, wax and grease using a grease and wax remover. Then let dry. **Do not scuff the surface prior to application.***

Surrounding areas do not have to be masked off. After application simply remove the product from the areas it is not desired by peeling or wiping away with a clean dry cloth. For personal safety it is recommended that headlights, taillights, and side mirrors be masked off when applying paint to any adjacent area. When using Custom Wrap on wheels, it is recommended to mask off the tires and calipers. Use at temperatures between 65°F (18°C) and 90°F (32°C) and when humidity is less than 70%. Do not apply paint in direct sun or windy conditions.

Shake can vigorously for one full minute after mixing ball moves freely. Shake can for 10 seconds after each minute of use.

To spray, hold can parallel and 6-10 inches from surface to be painted and use in an even, sweeping motion. Apply 1 thin light coat of Custom Wrap followed by 4-5 medium coats. It is recommended to apply 4-6 coats for an easy removal. The addition of more coats will increase the ease of removal even further. Allow 10 minutes between coats. Dries to the touch in 30 minutes. Can be handled in 1 hour. Recoat at any time. Covers approximately 12-14 square feet.

To clean a surface that has been coated with Custom Wrap, use a touchless car wash or wash by hand.

To remove Custom Wrap use fingers to peel up the edge of the dried product. Continue to peel product until completely removed. For optimal peel it is recommended that Custom Wrap be removed or recoated approximately 6 months after initial application. Areas where Custom Wrap coverage was applied too light can be removed with a clean dry cloth by wiping in a back and forth motion.

Packaging

Fill Weight: 11 oz

Per Case: 6 cans

Case Weight: 5.8 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans