

Product Description

Dupli-Color® Self-Etching Primer etches and primes in one easy step. Perfect for spot repairs. A high-quality formulation creates superior adhesion on most plastics, fiberglass, bare steel, and aluminum.

Product Characteristics

Color: Green

Properties

Product Weight: 6.58 lb/gal
Flash Point: Propellant < 0° F

Uses

Spot Repairs & Priming

Surfaces:

Plastic, Fiberglass, Bare Steel,
Stainless Steel, & Aluminum.

Packaging

Fill Weight: 12 oz
Per Case: 6 cans
Case Weight: 6.07 lbs
Cases/Pallet: 156
Units/Pallet: 936 cans

Application

Prepare surface by removing rust, scale, dirt, grease, etc. Wash with mild detergent, rinse well, and dry with a clean cloth. Lightly sand surface with 400-grit sandpaper, wet or dry. Soak the sandpaper in water and keep it wet while sanding. Wipe surface clean.

Mask-off areas to be protected from overspray. Use at room temperature (70° F) for best results. Do not paint on days when humidity is high.

Shake until ball inside breaks loose and rattles. Then hold can at top, and swing bottom of can in a circle for two minutes, making ball travel around bottom groove. Shake up and down occasionally. (Repeat shaking procedure for 10 seconds after each minute of spraying).

To spray, hold can 8-10 inches from surface. Use steady, even strokes, keeping can parallel to the surface throughout the stroke. Spray 2 to 3 thin coats, allowing etching filler to dry 2 minutes between coats. Repeat until area is built up. After final coat, allow etching filler to dry 30 minutes, before sanding with 400-grit sandpaper or applying the topcoat.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.