Automotive Metallic

Product Description

Dupli-Color® Automotive Metallic provides a brilliant metallic finish.

Product Characteristics

Colors: Gold & Chrome.

Finish: Metallic

Properties

Product Weight: 6.24 lb/gal
Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Automotive Metallic provides optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax Remover
Coat	CS101	Chrome
	GS100	Gold

Refer to the application box for more specific instructions!

Uses

Automotive Trim, Accessories, & Moldings.

Surfaces:

Surfaces for interior and exterior application.

Application

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover to clean surface. Scuff/sand surface with a red Scotch-Brite pad or equivalent. Wash with mild soap and water. Rinse well, and dry with a clean cloth.

Mask-off surrounding area to protect from overspray. Use at temperatures between 60°-92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs and sags apply 2-3 light coats, allowing surface to dry 10 minutes between each coat. Dries to the touch in 30 minutes. Can be handled in one hour. Covers approximately 12-14 square feet.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.

Packaging

Fill Weight: 11 oz
Per Case: 6 cans
Case Weight: 6.06 lbs
Cases/Pallet: 156
Units/Pallet: 936 cans