# Sandable Primer

**DAP1687, 1689,1692,1694,1698**

## Product Description

**Dupli-Color® Sandable Primer** is an all purpose fast drying primer that can be sanded to a smooth finish to help achieve uniformity. It is great for smooth fill-in of surface cracks and imperfections and is effective on both painted and unpainted surfaces.

## Product Characteristics

**Colors:** Rust Resistant, Gray Hot Rod, Black Hot Rod, White, & Red Oxide.

## Properties

**Product Weight:** 6.28 lb/gal
**Flash Point:** Propellant < 0° F

## Preferred Application

Dupli-Color Sandable Primer provides an optimal performance when this application method is followed.

| | | |
|---|---|---|
| **Prep** | PW100 | Prep Wipe |
| | PS100 | Prep Spray |
| | CM541 | Grease & Wax Remover |
| **Prime** | DAPxxxx | Sandable Primer |

***Refer to the application box for more specific instructions!***

## Uses

Fills in Surface Cracks & Imperfections.

*Surfaces:*

Fiberglass, Wood, & Metal.

## Application

*Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease and Wax Remover to clean surface. Sand surface with 320-grit sandpaper, wet or dry. Wash with mild soap and water. Rinse well and dry with a cloth.*

Mask off surrounding areas to protect from overspray. Use at temperatures between 60°-92° F, and when humidity is less than 60%.

Shake the can vigorously for one full minute after mixing ball moves freely. After each minute of use, the can needs to be shaken for an additional 10 seconds. To spray, hold the can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs and sags, apply in light coats. Allow surface to dry 10 minutes between coats and 30 minutes before sanding or application of finishing coat of paint. *If needed, sanding can be done wet or dry after 30 minutes with 600 grit sandpaper.* After sanding, if scratch is not filled, repeat the process. (***Note:*** Product is not recommended for use on damaged areas more than 1/16'' deep) Can be handled after 1 hour. Covers approximately 12 to 14 square feet.

The EZ Touch ™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.

## Packaging

**Fill Weight:** 12 oz
**Per Case:** 6 cans
**Case Weight:** 6 lbs
**Cases/Pallet:** 156
**Units/Pallet:** 936 cans