Metalcast™

Product Description

Dupli-Color® Metalcast™ is an anodized color coating that turns ordinary chrome pieces into a bright, transparent-colored metallic finish in an easy one-step process. It is a durable enamel finish that is oil, gas, and heat resistant (up to 500° F). Specially formulated to work over properly prepared shiny bare metal, and faux chrome-like surfaces.

Ideal for interior, exterior, and high-heat applications under the hood.

Product Characteristics

Base: Ground Coat (non-chrome like surfaces)

Anodized Colors: Red, Blue Yellow, Green, Purple, Orange, & Smoke

Finish: Metallic

Properties

Product Weight: 6 lb/gal
Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Metalcast provides optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax Remover
Prime	CP199	Adhesion Promoter
Extra	MC100	Ground Coat
Coat	MCxxx	Metalcast

MC100 is only used on non-chrome like surfaces!
Refer to the application box for more specific instructions!

Application

Prepare surface by removing loose paint, dirt, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover to clean surface. Wash with mild soap and water. Rinse well, and dry with a clean cloth.

Mask-Off surrounding area to protect from overspray. For added surface adhesion, use Dupli-Color Adhesion Promoter (CP199) first. If the surface is not chrome like in appearance, use Dupli-Color Metalcast Ground Coat (MC100) prior to color coat surface.

Use at temperatures between 60°-92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs and sags, apply 2 light coats, followed by one medium wet coat. Apply all coats within 1 hour, allowing 10 minutes between each coat. For additional coats after 1 hour, wait 7 days for paint to cure. Dries to the touch in 1 hour. Can be handled in 3 hours. Covers approximately 12-14 square feet.

Packaging

Fill Weight: 11 oz
Per Case: 6 cans
Case Weight: 6 lbs
Cases/Pallet: 156
Units/Pallet: 936 cans

Uses

Chrome Pieces

Surfaces:

Prepared Shiny Bare Metal & Chrome-like Surfaces.