Primer Sealer

Product Description

Dupli-Color® Primer Sealer creates a smooth uniform surface for final coating by completely sealing the primed surface. Provides maximum corrosion resistance and improves bonding of base colors on all metal, wood, and fiberglass surfaces.

Product Characteristics

Colors: Gray

Properties

Product Weight: 6.33 lb/gallon
Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Primer Sealer provides optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	CM541	Grease & Wax Remover
Coat	DAP1699	Primer Sealer

Refer to the application box for more specific instructions!

Packaging

Fill Weight: 12 oz
Per Case: 6 cans
Case Weight: 6 lbs
Cases/Pallet: 156
Units/ Pallet: 936 cans

Application

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover to Clean surface. Lightly sand surface with 400-grit sandpaper, wet or dry. Wash with mild soap and water. Rinse well, and dry with a clean cloth.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60°-92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs and sags apply 2-3 light coats, allowing surface to dry 10 minutes between coats. Dries to the touch in 30 minutes. Can be handled in 1 hour. Covers approximately 12-14 square feet. Once primer application is complete, follow with Dupli-Color Color Coat.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.

Uses

Improves bonding of base colors on any of the surfaces mentioned below.

Surfaces:

Fiberglass, Wood, & Metal.