



Paintable Rubberized Undercoating

UC101

Product Description

Dupli-Color® Paintable Rubberized Undercoating is ideal for providing protection for wheel wells, gas tanks, frames & supports, weld joints, floor pans, doors, and quarter panels. This offers economical protection, paintability, moisture resistance, corrosion resistance, and a durable rubberized finish.

Ideal use on vehicle underbodies and trailers.

Product Characteristics

Color: Black

Properties

Product Weight: 7.38 lb/gal

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Paintable Rubberized Undercoating provides optimum performance when you use this application method.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax Remover
Coat	UC101	Paintable Undercoating

Refer to the application box for more specific instructions!

Application

Directions-Prep: Clean surfaces by removing dirt, oil, grease, wax, rust, and loose paint. Thoroughly clean with mild detergent and dry with a clean cloth.

Mask surrounding areas to protect from overspray.

Spray: Shake well before using (3 minutes). Use temperatures above 70° F. Do not spray when humidity is high. Use in well ventilated area. Hold can 12-16 inches from surface to be sprayed. Allow 10 minutes to dry.

Accidental overspray should be wiped off immediately with a mild solvent. Clear nozzle by inverting can upside down and spraying until clear gas comes out.

Packaging

Fill Weight: 16 oz

Per Case: 12 cans

Case Weight: 16.75 lbs

Cases/Pallet: 54

Units/Pallet: 648 cans

Uses

Wheel Wells, Gas Tanks, Frames & Supports, Weld Joints, Floor Pans, Doors, and Quarter Panels. (Used on Vehicle Underbodies and Trailers).

Surfaces:

Metal, Aluminum, Fiberglass, & Plastic.