

Product Description

Dupli-Color® Caliper Paint Kit provides the tools to apply a durable protective coating resistant to chipping, brake dust, and automotive chemicals. Formulated with Ceramic resins, this coating resists temperatures up to 500° F. This paint is resistant to chipping, chemicals, and paint dust.

The kit contains a Caliper Paint Pint, Caliper Aerosol Cleaner, Stir Stick, Paint Brush, Masking Tape, and Step-by-Step Instruction Booklet.

Product Characteristics

Colors: Red, Racing Black Satin, Silver, & Gloss Black.

Finish: Gloss & Satin.

Properties

Product Weight: 14.61 lb/gal

Flash Point: 40° F PMCC (Paint)
1° F PMCC (Cleaner)

Preferred Application

Dupli-Color Caliper Paint Kit provides the optimum performance when this application method is followed.

Prep	BCP200	Caliper Cleaner
Coat	BCPxxx	Caliper Paint Kit

Refer to the application box for more specific instructions!

Uses

Brake Calipers, Rotors, & Drums.

Surfaces:

Metal

Application

Step 1: Remove all four wheels from vehicle. Calipers and/or drums do not need to be removed. For best results, unbolt caliper and remove brake pads. Do not remove brake line.

Step 2: Clean surfaces to be painted with enclosed Dupli-Color Caliper Cleaner. Read directions and precautionary wording before use. Spray surface with Caliper Cleaner.

Step 3: Scrub Caliper Cleaner on caliper with a clean toothbrush or something equivalent to it. Wipe dry with a clean towel. Be sure to remove all brake dust and/or contaminants, before application.

Step 4: Masking of the surrounding area is recommended. Tape off the brake bleeder screw, brake lines, and caliper piston boots.

Step 5: Read paint label directions and precautionary wording carefully. Remove lid from paint can. Stir contents thoroughly for 1 minute with enclosed stir stick.

Step 6: Apply paint to the caliper or drum with enclosed brush in thin, even strokes. Allow Paint to set-up for 15-20 minutes between coats. Apply additional coats as needed to even out brush strokes and obtain full coverage.

Paint requires 2 hours to dry, before installing wheels. Allow 24 hours for paint to fully cure prior to vehicle use.

Use of rubber gloves is recommended.

Packaging

Fill Weight: 16 oz

Per Case: 2 kits

Case Weight: 4 lbs

Cases/Pallet: 192

Units/Pallet: 384 cans