Professional Undercoat & Sound Eliminator

UC102

Product Description

Dupli-Color® Professional Undercoat and Sound Eliminator is ideal for providing protection for wheel wells, gas tanks, frames & supports, weld joints, floor pans, doors, and quarter panels. This provides superior protection by reducing road vibrations and road noise.

Product Characteristics

Color: Black

Properties

Product Weight: 9.15 lb/gal
Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Professional Undercoat and Sound Eliminator provides an optimal performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax Remover
Coat	UC102	Professional Undercoat & Sound Eliminator

Refer to the application box for more specific instructions!

Application

Prep: *Clean surfaces by removing dirt, oil, grease, wax, rust, and loose paint. Thoroughly clean with a mild detergent and dry with a clean cloth. Mask surrounding areas to protect from overspray.*

Spray: Shake well before using (approximately 3 minutes). Use at temperatures above 70° F. Do not spray when humidity is high. Use in well ventilated area. Hold can 12-16 inches from the surface to be sprayed. Allow 10 minutes to dry.

Accidental overspray should be wiped off immediately with a mild solvent. Clear nozzle by inverting upside down and spraying until a clear gas comes out.

Packaging

Fill Weight: 17 oz
Per Case: 12 cans
Case Weight: 18 lbs
Cases/Pallet: 54
Units/Pallet: 648 cans

Uses

Wheel Wells, Gas Tanks, Frames & Supports, Weld Joints, Floor Pans, Doors, and Quarter Panels. (Ideal on vehicle underbodies and trailers)

Surfaces:

Fiberglass, Wood, Metal, Plastic, & Aluminum.