



Perfect Match™

BUNxxx, BCCxxx, BFMxxx,
BGMxxx, BHAxxx, BHYxxx,
BKAxxx, BNSxxx, BMZxxx,
BSUxxx, BTYxxx, BVWxxx

Product Description

Dupli-Color® Perfect Match™ is a fast drying Acrylic Lacquer specialty formulated to match OEM automotive paint colors.

Product Characteristics

There are a variety of colors available.

- Gray Scratch Filler Primer
- Three Universal Black Colors
- Various OEM Exact Match Colors
- Clear Top Coat

Properties

Product Weight: 6.26 lb/gal

Flash Point: Propellant < 0° F

Preferred Application Method

Dupli-Color Perfect Match provides the ultimate touch-up when this application method is followed.

Prep	CM541	Grease & Wax Remover
Prep	CM541	Grease & Wax Remover
Prime	BPR0031S	Gray Scratch Filler Primer (as needed)
Coat	OEM #	Perfect match
	Universal	Perfect match
Clear	BCL0125	Clear Coat

*Sanding needs to occur between 1st & 2nd Prep step.
Refer to the application box for more specific
instructions!*

Uses

Automotive Exterior Paint Surfaces (Ex:
Large Touch-ups & Vehicle Accessories).

Surfaces:

Metal, Fiberglass, Aluminum, & Plastic.

Application

Caution: For maximum product performance read entire label and directions prior to paint application.

Use a clean cloth to wipe down surface with rubbing alcohol or Grease & Wax Remover. Lightly sand surface with a scuff pad or 600 grit sand paper. Wipe the surface again with a clean cloth using rubbing alcohol or Grease & Wax Remover. If bare metal is exposed use Dupli-Color® Perfect Match Scratch Filler Primer prior to color coat.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60° F (16°C) and 95°F (35°C), and when humidity is less than 80%.

Shake can vigorously for one full minute after mixing ball moves freely and 10 seconds after each minute of use. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs or sags, apply in 2-3 light coats or until even coverage is achieved. Allow paint to dry 10 minutes between coats and 30 minutes before applying Dupli-Color® Perfect Match Protective Clear Coat Finish. Covers approximately 10-12 square feet.

The EZ 360 Touch dial adjusts to spray horizontally, vertically, or any angle for precise control without finger fatigue for a perfect finish.

Packaging

Fill Weight: 8 oz

Per Case: 6 cans

Case Weight: 4.74 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans